



# C100

GIS SYSTEM

---



# C100 Data Controller

The C100 control terminal is a multi-functional data controller specially designed for the surveying industry. It has an impressive battery life of up to 15 hours. The 5.5-inch sun readable display screen and IP67 protection level make it suitable for various harsh outdoor conditions. The powerful 8-core processor and Android 11 operating system ensure that the C100 runs efficiently and smoothly, and is compatible with various measurement software applications, making it the ideal companion for your surveying tasks.



LENGTH	WIDTH	HEIGHT	WEIGHT
221mm	77.7mm	16mm	370g



## SUNLIGHT-READABLE SCREEN

With 5.5 inch high-resolution sun-proof screen, you can see clearly under the sun.



## ULTRA-LONG ENDURANCE

C100 controller is equipped with a long-life battery which ensures you a 15h of operation without stopping.



## DUAL NETWORK DUAL STANDBY

With 4G all netcom communications and dual Sim card option, you can work all day and still remain contactable anytime, anywhere.



## HIGH-PERFORMANCE CPU

Eight-core high performance processor enable you to deal with all complicated processing.

# ITEM

# SPECIFICATION

<b>SYSTEM</b>	Operating system CPU Memory External storage	Android 11 8-core 2.0GHz processor 3GB RAM + 32GB ROM Micro SD, up to 256GB
<b>PHYSICAL PARAMETERS</b>	Display Touch Panel Camera Sensors Notification Audio Interface	Screen size: 5.5-inch Resolution: 720*1440px 5-point capacitive touch Rear 13MP, Support Flash light, Support Auto focus Magnetometer, Accelerometer and Ambient Light Sensor Audio, Vibration and LED Indicators Speaker with a volume of 95dB±3, equipped with 1 microphone Type-C(supports OTG) SIM: Equipped with ESIM (SIM1) and one Nano SIM card slot (SIM2) as standard
<b>DATA COMMUNICATION</b>	Bluetooth WIFI Network GNSS NFC	BT5.0(BLE) IEEE: 802.11 a/b/g/n/ac Dual-baud: 2.4G/5G FDD-LTE B1/B3/B5/B7/B8 TDD-LTE B38/B39/B40/B41 WCDMA B1/B2/B5/B8 GSM B2/B3/B5/B8 CDMA/ EVDO BC0/BC1 GPS/GLONASS/BDS Supported NFC Protocols: ISO14443A/B, ISO15693 Data Reading Distance: 0~5cm
<b>ELECTRICAL</b>	Battery (non-removable)	7700mAh (Support Rapid Charging) Working time: 15 hours Charging time: ≤4 hours
<b>PHYSICAL</b>	Dimension(mm) Weight(g)	221*77.7*16 370
<b>ENVIRONMENT</b>	Working Temperature Storage Temperature Work Humidity Shock Protection ESD	20°C~55°C -30°C~70°C 5%~95% 1.5M drop onto concrete IP68 Air discharge: ±15kV    Contact discharge: ±8kV

► Manufacturers may update parameters at any time, please refer to the latest product information.